

BANDSAW SHARPENERS

MANUAL RB12 Standard RB12M / MSA RB12VMP

DinaSaw's Bandsaw Sharpeners allow you to improve your saw's cutting efficiency by optimising tip angles and chip removal meaning blades cut faster, more accurately and stay sharper longer.

DinaSaw's Manual Bandsaw Sharpeners come in 2 models, Standard and MSA. Unlike normal sharpeners that can only sharpen perpendicular to the blade, DinaSaw's MSA sharpeners can also sharpen with a positive 10° angle across the set teeth's tips, enhacing cutting and sawdust extraction while decreasing frictional heat.

Angling the saw's set teeth cutting face produces larger chips that are directed towards the centre so they are better retained in the gullet as opposed to standard, straight teeth that generate smaller chips that are forced directly down to spill beside the blade causing friction that can heat and buckle the blade.

SHARPENING EQUIPMENT

THE FEATURES

- > Easy screw adjustments
- Cast aluminium grinder motor arm for rigidity and accuracy
- Sealed ball bearings, case hardened cams and pivots
- > High efficiency 12v motors
- > Unique magnetic blade clamping
- > Free standing Tripod frame
- Avaliable in Standard (straight teeth) and MSA (bevel sharpening)
- > Can utilise ABN / CBN grinding wheels

THE BENEFITS

- Faster, more accurate cutting.
- Better tooth penetration.
- Less sawdust remains on lumber.
- Less trictional heat.
- Saws stay sharper longer.
- Teeth require less set.



MANUAL RB12

SPECIFICATIONS		
Operation	Hand Crank	One turn per tooth
MSA	Optional	Positive 10° angle
Saw Blade	Width	Min. 16mm (5/8")
		Max. 76mm (3")
	Tooth Pitch	Min. 8mm (5/16")
		Max. 32mm (11/4")
Weight	Std. Gross	21kg (43lbs)
Feed	Mechanical	Cam operated - Variable stroke
Grind Wheel (ABN / CBN)	Diameter	125mm (5")
	Speed	6500 rpm
Mounting	Machine	Tripod Stand
	Blade	Adjustable Frame
Power Required	12 - 15 vdc	Optional mains power supply available

PROUDLY MANUFACTURED IN AUSTRALIA

SHARPENING EQUIPMENT





